



型号	Type	CI8.3	CI8.5	CI10	CI15	CI17	
尺寸 Dimension (mm)	A	28.80±0.50	28.80±0.50	23.10±0.25	26.10±0.50	22.90±0.25	
	B	21.60min	21.60min	20.30±0.20	22.10 ^{+0.30} _{-0.15}	18.90±0.20	
	C						
	D	2.70±0.15	3.20±0.15	7.40±0.15	12.40 ^{+0.30} _{-0.20}	13.25±0.20	
	E	3.60±0.10	3.60±0.10	2.30±0.10	3.60±0.10	3.70±0.10	
	E-F	2.05±0.10	2.35±0.10	1.10±0.10	1.25 ^{+0.15} _{-0.10}	2.00±0.15	
	A1	29.50±0.50	29.50±0.50	23.10±0.25	26.10 ^{+0.60} ₀	22.90±0.25	
	D1	3.15±0.15	3.50±0.10	7.40±0.15	9.80 ^{+0.05} _{-0.10}	13.25±0.25	
G	1.75±0.05	2.20±0.05	1.20±0.05	1.80±0.05	2.00±0.05		
磁芯常数 C _i (mm ⁻¹) Core Factor		9.71	7.15	6.45		1.791	
有效磁路长度 l _e (mm) Effective Length l _e		55.27	55.44	48.5		48.19	
有效截面积 A _e (mm ²) Effective Area		5.69	7.75	7.52		26.9	
有效体积 V _e (mm ³) Effective Volume		314.49	429.66	585.26		1669.47	
重量 w Weight(g)		1.61	2.05	1.95		6.2	
电感系数 A _L (nH/N ²)	HP40	300±25%	400±25%	380±25%	765±25%	1392±25%	
	HP44						
	HB5K						
	PA7K						
	PA10K						
	PA15K						