



型号	Type	FUI8.3	FUI9.8	FUI12	FUI15	FUI29	
尺寸 Dimension (mm)	A	27.40±0.50	23.80±0.30	21.00±0.30	19.70±0.30	28.00±0.30	
	B	22.40±0.50	19.20±0.30	16.20±0.15	15.60±0.30	20.45±0.15	
	C						
	D	8.30±0.20	9.80±0.20	11.80±0.25	14.80±0.30	16.60±0.25	
	D1	6.50±0.15	7.30±0.20	8.90±0.20	11.40±0.25	12.75±0.15	
	D2	5.40±0.10	5.70±0.10	7.00±0.10	7.00±0.10	9.80±0.20	
	E	2.95±0.05	3.85±0.05	3.50±0.10	4.60±0.10	3.70±0.15	
	E-F	1.05±0.15	1.30±0.10	2.30±0.10	1.80±0.05	1.80±0.10	
	X	28.30±0.50	24.10±0.30	21.80±0.30	19.90±0.30	28.60±0.30	
	Y	3.85±0.10	4.40±0.10	5.50±0.20	4.45±0.15	7.90±0.20	
Z	1.35 <sup>+0.05</sup> <sub>0</sub>	2.00 <sup>+0.05</sup> <sub>0</sub>	1.80 <sup>+0.10</sup> <sub>0</sub>	4.45 <sup>+0.15</sup> <sub>0</sub>	1.90 <sup>+0.10</sup> <sub>0</sub>		
磁芯常数 C <sub>1</sub> (mm <sup>-1</sup> ) Core Factor		9.33	5.96	4.04	4.60		
有效磁路长度 l <sub>e</sub> (mm) Effective Length l <sub>e</sub>		53.6	44.88	40.82	42.5		
有效截面积 A <sub>e</sub> (mm <sup>2</sup> ) Effective Area		5.19	7.52	10.08	10.5		
有效体积 V <sub>e</sub> (mm <sup>3</sup> ) Effective Volume		589	337.49	411.46	585		
重量 w Weight(g)		1.55	2.33	2.35	2.64		
电感系数 A <sub>L</sub> (nH/N <sup>2</sup> )	HP40	250±25%	370±25%	400±25%	500±25%	450±25%	
	HP44						
	HB5K						
	PA7K						
	PA10K						
	PA15K						